

LED 160



This all-round LED 160 Marine Lantern has world-class optical performance with options for buoys and fixed installations. Three different lens options available covering a range from 3 NM up to 12NM ($T_c = 0,74$).

[Contact Us](#) [Get a quote](#)

Rating: Not Rated Yet

[Ask a question about this product](#)

Description

[Features](#)

Marine Lantern LED 160 features:

- Standard IALA colours red, green, white and yellow
- Best in class optical performance
- New designed rugged injection moulded aluminium housing
- Easy field installation thanks to the integrated junction box with 3 cable entries
- Extremely low power consumption, suitable for solar and battery operation
- Integrated 16A solar panel charger
- Adjustable intensity and range
- The lantern is available in three different versions. LED 160 with Narrow 5° and with Wide 10° vertical divergence, and the LED

160H with a 2,5° vertical divergence

- Programmable with Sabik standard IR programmer or with Bluetooth® Control from up to 50m distance
- Optional integrated GNSS synchronization
- Optional integrated LTE-M/GNSS remote monitoring
- Available with integrated AIS

[Downloads](#)

Downloads

[_pdf Product Datasheet LED 160 \(pdf eng\) \(3.08 MB\)](#)

[_pdf Product Datasheet LED 160 \(pdf ES\) \(214 KB\)](#)

[Product Datasheet LED 160 \(pdf RU\)](#)

[Video on Sabik Bluetooth® Control](#)

[Extranet login](#)

Extranet login